





SENDER 12
CW, quadratisch, PHASE





220-240V ~50/60Hz | 200mA
Systemleistung: 8,2W
Material: Aluminium

SENDER 18
CW, quadratisch, PHASE



220-240V ~50/60Hz | 350mA
Systemleistung: 12W
Material: Aluminium

SENDER 24
CW, quadratisch, PHASE



220-240V ~50/60Hz | 500mA
Systemleistung: 15W
Material: Aluminium

1003017, 1004703	480lm 440lm 3000K 4000K	

Variante	Art. Nr.	EUR
480lm 3000K CRI80 <input type="checkbox"/> weiß	1003017	74,00
440lm 4000K CRI80 <input type="checkbox"/> weiß	1004703	74,00

1003018, 1004704	880lm 880lm 3000K 4000K	

Variante	Art. Nr.	EUR
880lm 3000K CRI80 <input type="checkbox"/> weiß	1003018	79,00
880lm 4000K CRI90 <input type="checkbox"/> weiß	1004704	79,00

1003019, 1004705	1200lm 1240lm 3000K 4000K	

Variante	Art. Nr.	EUR
1200lm 3000K CRI90 <input type="checkbox"/> weiß	1003019	85,00
1240lm 4000K CRI90 <input type="checkbox"/> weiß	1004705	85,00